

Dulux Avista Concrete Sealer Slip Reducing Additive



Fine white slip reducing granules

Description

Fine white granules.

Uses

- To increase the slip resistance of sealers on floors.
- For use in all Dulux Avista Sealer Ranges.

Advantages

- Disperses readily and evenly through sealer.
- Slow to settle or float in sealer.
- Polymeric in nature, therefore, more compatible physically with sealers e.g. expansion / contraction.
- Generally increases abrasion resistance of sealers.
- Compatible with solvent and water based systems.

Properties

Appearance:	White granules
Density (g/cc) @ 25°C:	0.90
Maximum Particle Size (microns):	840
Flash Point:	> 277°C

Mixing Instructions

Mixing Quantities

250 grams to 10 litres or 500 grams to 20 litres.

Mixing

Pour into sealer slowly, while mixing with a hand paddle.

Application

- Apply only into final coat of sealer.
- To avoid settling, stir thoroughly every 2 minutes.

Roller application

- Sealer must be roller applied from a roller tray. Do not broom apply.
- Avoid excess SRA build up on the edges of the roller. This can lead to roller lines in the surface.
- To enhance slip resistance, sealer must be applied thinly, at approximately 15m² per litre.

Limitations

- If left in some solvent type sealers for an extended period (> 4 hours), there is a tendency for swelling and sticking together of particles.
- As with most materials it will slowly wear, hence periodic check of slip resistance is advisable.
- Dulls gloss retention.

Supply

FD278014-250G AVS SLIP RES ADDITIVE POWDER 250G

Important notice

A Safety Data Sheet (SDS) and Technical Data Sheet (TDS) are available from the Dulux Avista website www.duluxavista.com.au. Read the SDS and TDS carefully prior to use as application or performance data may change from time to time. In an emergency, contact any Poisons Information Centre (Telephone 131 126 within Australia) or a doctor for advice.

Product disclaimer

This Technical Data Sheet (TDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Dulux Avista does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.



Dulux Avista
1956 Dandenong Road, Clayton VIC 3168 Telephone:
1800 801 108
ABN 80 069 961 968

Distributed in New Zealand by: Concrete Plus Limited
150 Hutt Park Road, Gracefield Ph: 0800 657 156